
## NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: RAVG ≤0.4% @ 425 - 675nm




5. Rohs Compliant

6. SURFACE FLATNESS (P-V):  $\lambda/4$  (per inch over clear aperture)







## PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	S2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	60-40	60-40		
CLEAR APERTURE	22.50 x 22.50	22.50 x 22.50		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED		

			Edmund Optics®	
THIRD ANGLE - PROJECTION		TITLE	25mm SQ., 4mm THICK, VIS 0° COATEI N-BK7 WINDOW	Ο λ/4
ALL DIMS IN	mm	DWG NO	49629	SHEET 1 OF

25mm \$Q., 4mm THICK, VIS 0° COATEI N-BK7 WINDOW	D λ/4
49629	SHEET 1 OF 1