

## NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: RABS ≤0.25% @ 880nm RAVG ≤1.25% @ 400 - 870nm RAVG ≤1.25% @ 890 - 1000nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V):  $\lambda/4$  (per inch over clear aperture)







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø36.00	Ø36.00
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

THIRD ANGLE PROJECTION	$\phi \Leftrightarrow$	TITL
ALL DIMS IN	mm	DW

	Edmund Optics®
777.5	40mm DIA., 4mm THICK, VIS-NIR COATED

	TITLE	40mm DIA., 4mm THICK, VIS-NIR COP λ/4 N-BK7 WINDOW	(IED
mm	DWG NO	48446	SHEET 1 OF 1