




NOTES:

- 1. SUBSTRATE:
ZERODUR®
- 2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN 30 ARCSEC
- 3. COATING (APPLY ACROSS CLEAR APERTURE)
S1: R(abs) >99.5% @ 266nm @ 45° AOI
R(avg) >99.5% @ 263 - 268nm @ 45° AOI
- DAMAGE THRESHOLD, BY DESIGN:
2.5 J/cm² @ 266nm, 20ns, 20Hz
- S2: NONE
- 4. FINE GRIND SURFACE
- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY
ACROSS CLEAR APERTURE
- 6. CLEAR APERTURE AND COATING APERTURE ARE CENTERED ON SURFACES



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2			 Edmund Optics®		
SHAPE	PLANO	PLANO					
SURFACE QUALITY	20-10	COMMERCIAL POLISH					
CLEAR APERTURE	Ø 9.00	N/A					
COATING APERTURE	Ø 9.00	N/A					
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED					