






- NOTES:
- 1. SUBSTRATE:
N-BK7
 - 2. COATING (APPLY ACROSS CLEAR APERTURE)

S1 & S2: NIR I (600-1050nm)
R(avg) ≤0.5% @ 600 - 1050nm
 - 3. FINE GROUND SURFACE
 - 4. POWER, IRREGULARITY, AND SURFACE QUALITY
SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
 - 5. ROHS COMPLIANT



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2	EFL	50.00	 Edmund Optics®		
SHAPE	CONVEX	PLANO	BFL	46.04			
RADIUS	25.84	∞			TITLE	30mm H x 30mm L x 50mm FL NIR I Coated, Illumination Grade PCX Cylinder Lens	
SURFACE QUALITY	60 - 40	60 - 40					
CLEAR APERTURE	29.00 x 29.00	29.00 x 29.00	ALL DIMS IN	mm	DWG NO	25503	SHEET 14 OF 16
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED					