


[All Products](#) / [Optics](#) / [Optical Filters](#) / [Dichroic Filters](#)

Extreme Ultraviolet (EUV) Dichroic Filters



- Separates EUV from the NIR Laser Source in High Harmonic Generation
- Designed for High Damage Thresholds
- Supports Applications from 10 – 40nm
- Available from Stock
- No Minimum Order Quantities, No Coating Lot Charges

Common Specifications

Physical & Mechanical Properties

Diameter (mm):	50.80	Thickness (mm):	5.08 ±0.1
Parallelism (arcmin):	<5	Dimensional Tolerance (mm):	+0.0/-0.2

Optical Properties

Angle of Incidence (°):	78	Substrate:	Fused Silica (Corning 7980)
Coating:	Dielectric Multilayer AR	Surface Quality:	20-10
Surface Figure, RMS:	<λ/10 @ 633nm		

Technical Information

Products

Dia. (mm)	Thickness (mm)	Wavelength Range (nm)	Stock Number	Price	Buy
50.80	5.08	10 - 25	#18-279	C\$7,345.80	3 In Stock
50.80	5.08	20 - 40	#18-280	C\$7,345.80	5 In Stock



Copyright 2023, Edmund Optics Inc., 101 East Gloucester Pike, Barrington, NJ 08007-1380 USA

Phone: 1-800-363-1992 :

www.edmundoptics.com